


DATI TECNICI

		Dimensioni										Capacità di carico				Peso	PROFILO-TIPO
TIPO ZZ	TIPO 2 RS	d mm	D mm	H mm	B mm	G mm	L mm	F mm	T mm	R mm	α	C KN	C ₀ KN	C _A KN	C _{0A} KN	Kg	
MR.000 ¹	-	30	52,5	33	17	5	27	6	40	15	15°	24	32	7	7	0,38	EC 053
MR.001 ¹	MR.021	30	62	37,5	20	8	30,5	7	42	20	20°	31	35,5	11	11,5	0,52	EC062 2890
MR.002 ¹	MR.022	35	70,1	44	23	10,5	36	8	48	22	20°	45,5	51	14	13	0,80	EC070 2867
MR.003	MR.023	40	77,7	48	23	10,5	36,5	11,5	54	24	20°	48	56,8	18	18	1,02	EC078 2810
MR.005	MR.025	45	88,4	57	30	10,5	44	13	59	26	20°	68	72	23	23	1,61	EC089 2811
MR.007	MR.027	60	107,7	69	31	20	55	14	71	34	20°	81	95	31	36	2,69	EC108 2862
MR.009	MR.029	60	123	72,3	37	14	56	16,3	80	40	20°	110	132	43	50	3,8	EC123 FI.123 - 2891
MR.010	MR.030	60	149	78,5	43	10,5	58,5	20	103	50	15°	151	192	68	71	6,65	EC.149 FM.149 - EC.149 2757
MR.191	-	60	149	86	45	16,5	67	19	107	50	15°	151	192	68	71	7,40	-

¹ Cuscinetto non lubrificabile