


## DATI TECNICI

		Dimensioni										Capacità di carico				Peso	PROFILO-TIPO
TIPO ZZ	TIPO 2 RS	d mm	D mm	H mm	B mm	G mm	L mm	F mm	T mm	R mm	$\alpha$	C KN	C <sub>0</sub> KN	C <sub>A</sub> KN	C <sub>0A</sub> KN	Kg	
MR.001/S <sup>°</sup>	MR.021/S	30	<b>64,8</b>	37,5	20	8	30,5	7	42	20	20°	31	35,5	11	11,5	0,52	<b>EC065L</b>
MR.002/S <sup>°</sup>	MR.022/S	35	<b>73,8</b>	44	23	10,5	36	8	48	22	20°	45,5	51	14	13	0,80	<b>EC074L</b>
MR.003/S	MR.023/S	40	<b>81,8</b>	48	23	10,5	36,5	11,5	54	24	20°	48	56,8	18	18	1,02	<b>EC082L</b>
MR.005/S	MR.025/S	45	<b>92,8</b>	57	30	10,5	44	13	59	26	20°	68	72	23	23	1,61	<b>EC093L</b>
MR.007/S	MR.027/S	60	<b>111,8</b>	69	31	20	55	14	71	34	20°	81	95	31	36	2,69	<b>EC112L</b>
MR.009/S	MR.029/S	60	<b>127,8</b>	72,3	37	14	56	16,3	80	40	20°	110	132	43	50	3,8	<b>EC128L</b>
MR.010/S	MR.030/S	60	<b>153,8</b>	78,5	43	10,5	58,5	20	103	50	15°	151	192	68	71	6,65	<b>EC154L</b>

<sup>°</sup> Cuscinetto non lubrificabile

