



**Motori asincroni trifase autofrenanti serie AT**  
**AT series three-phase induction brake motors**  
**Moteurs asynchrones triphasés autofreinants série AT**  
**Asynchrone Drehstrombremsmotoren Serie AT**

**6 POLI** 1000 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∅	Watt	Kg	Nm	∅	VA	Kg	Nm	∅	Watt	Kg	Nm	∅	Watt	Kg
AT56B	1	21500	12	4,0	-	-	-	-	-	-	-	-	-	-	-	-
AT56C	1	21500	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63B	4	18000	20	5,0	5	18000	40	5,0	3	18000	17	5,0	7,5	18000	11,5	4,4
AT63C	4	18000	20	6,0	5	18000	40	6,0	3	18000	17	6,0	7,5	18000	11,5	4,6
AT71A	4	25000	20	7,0	5	25000	40	7,0	4	25000	17	7,0	7,5	25000	11,5	6,3
AT71B	4	25000	20	8,0	5	25000	40	8,0	4	25000	17	8,0	7,5	25000	11,5	6,6
AT71C	4	24000	20	8,0	5	24000	40	8,0	4	24000	17	8,0	7,5	24000	11,5	7,1
AT80A	8	16000	25	11,0	10	16000	70	11,0	9	16000	34	11,0	15,0	16000	16,0	9,8
AT80B	8	16000	25	13,0	10	16000	70	13,0	9	16000	34	13,0	15,0	16000	16,0	11,6
AT80C	8	15000	25	14,0	10	15000	70	14,0	9	15000	34	14,0	15,0	15000	16,0	12,1
AT90S	16	15000	30	17,0	20	15000	120	17,0	10	15000	34	15,0	30,0	15000	16,0	14,0
AT90L	16	13500	30	18,0	20	13500	120	18,0	10	13500	34	17,0	30,0	13500	16,0	16,0
AT90LB	16	13000	30	19,5	20	13000	120	19,5	10	13000	34	18,5	30,0	13000	16,0	18,0
AT100A	32	10000	40	26,0	40	10000	160	28,0	12	10000	40	23,0	60,0	10000	21,0	23,0
AT100B	32	7500	40	28,0	40	7500	160	30,0	12	7500	40	25,0	60,0	7500	21,0	24,5
AT100BL	32	7000	40	30,0	40	7000	160	32,0	12	7000	40	27,0	60,0	7000	21,0	26,5
AT112A	60	6000	50	39,0	60	6000	300	39,0	13	6000	40	40,0	120,0	6000	21,0	36,0
AT112B	60	5500	50	46,0	60	5500	300	46,0	13	5500	40	41,0	120,0	5500	21,0	43,0
AT132S	80	1600	55	56,0	90	1600	500	57,0	17	1600	40	48,0	240,0	1600	28,0	55,0
AT132M	80	1350	55	65,0	90	1350	500	66,0	17	1350	40	57,0	240,0	1350	28,0	64,0
AT132ML	80	1100	55	68,0	90	1100	500	69,0	17	1100	40	60,0	240,0	1100	28,0	67,0
AT160M	150	1000	85	89,0	200	1000	600	85,0	30	1000	65	77,0	480,0	1000	38,0	91,0
AT160L	150	850	85	102,0	200	850	600	105,0	30	850	65	97,0	480,0	850	38,0	111,0
AT180L	260	200	100	144,0	400	200	600	144,0	-	-	-	-	480,0	650	38,0	146,0
AT200LA	400	100	100	159,0	400	100	600	159,0	-	-	-	-	480,0	450	38,0	161,0
AT200LB	400	100	100	179,0	400	100	600	179,0	-	-	-	-	480,0	450	38,0	181,0