



**Motori asincroni trifase autofrenanti serie AT**  
**AT series three-phase induction brake motors**  
**Moteurs asynchrones triphasés autofreinants série AT**  
**Asynchrone Drehstrombremsmotoren Serie AT**

**2 POLI** 3000 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∅	Watt	Kg	Nm	∅	VA	Kg	Nm	∅	Watt	Kg	Nm	∅	Watt	Kg
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
AT56A	1	9700	12	4,0	-	-	-	-	-	-	-	-	-	-	-	-
AT56B	1	8900	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63A	4	8100	20	5,0	5	8100	40	5,0	3	8100	18	5,0	7,5	8100	11,5	4,3
AT63B	4	6750	20	6,0	5	6750	40	6,0	3	6750	18	6,0	7,5	6750	11,5	4,9
AT63C	4	5400	20	7,0	5	5400	40	7,0	3	5400	18	7,0	7,5	5400	11,5	6,2
AT71A	4	5400	20	8,0	5	5400	40	8,0	4	5400	18	7,0	7,5	5400	11,5	6,4
AT71B	4	5400	20	8,0	5	5400	40	8,0	4	5400	18	8,0	7,5	5400	11,5	6,8
AT71C	4	5500	20	9,0	5	5500	40	9,0	4	5500	18	9,0	7,5	5500	11,5	8,0
AT80A	8	5400	25	11,0	10	5400	70	11,0	9	5400	25	11,0	15,0	5400	16,0	9,6
AT80B	8	5400	25	12,0	10	5400	70	12,0	9	5400	25	12,0	15,0	5400	16,0	10,9
AT80C	8	5100	25	13,0	10	5100	70	13,0	9	5100	25	13,0	15,0	5100	16,0	11,6
AT80D	8	4900	25	14,0	10	4900	70	14,0	9	4900	25	14,0	15,0	4900	16,0	12,6
AT90S	16	4000	30	17,0	20	4000	120	17,0	10	4000	25	14,0	30,0	4000	16,0	14,0
AT90L	16	4000	30	18,0	20	4000	120	18,0	10	4000	25	15,0	30,0	4000	16,0	15,5
AT90LB	16	3800	30	20,0	20	3800	120	20,0	10	3800	25	18,0	30,0	3800	16,0	17,5
AT100A	32	2500	40	25,0	40	2500	160	27,0	12	2500	35	22,0	60,0	2500	21,0	22,0
AT100B	32	2400	40	28,0	40	2400	160	30,0	12	2400	35	25,0	60,0	2400	21,0	24,5
AT112A	60	1500	50	36,0	60	1500	300	36,0	13	1500	35	31,0	120,0	1500	21,0	33,0
AT112B	60	1400	50	41,0	60	1400	300	41,0	13	1400	35	36,0	120,0	1400	21,0	38,0
AT112BL	60	1300	50	43,0	60	1300	300	43,0	13	1300	35	38,0	120,0	1300	21,0	40,0
AT132S	80	430	55	58,0	90	430	500	59,0	17	430	35	50,0	240,0	430	28,0	57,0
AT132SL	80	430	55	61,0	90	430	500	62,0	17	430	35	58,0	240,0	430	28,0	60,0
AT132M	80	400	55	67,0	90	400	500	68,0	17	400	35	59,0	240,0	400	28,0	66,0
AT132ML	80	400	55	71,0	90	400	500	72,0	17	400	35	63,0	240,0	400	28,0	70,0
AT160MA	150	300	85	95,0	200	300	600	93,0	30	300	65	82,0	480,0	300	38,0	96,0
AT160MB	150	300	85	108,0	200	300	600	106,0	30	300	65	95,0	480,0	300	38,0	109,0
AT160L	150	300	85	111,0	200	300	600	117,0	30	300	65	106,0	480,0	300	38,0	120,0
AT180M	260	200	100	119,0	400	200	600	130,0	-	-	-	-	480,0	200	38,0	131,0
AT200LA	400	100	100	149,0	400	100	600	150,0	-	-	-	-	480,0	100	38,0	151,0
AT200LB	400	100	100	169,0	400	100	600	170,0	-	-	-	-	480,0	100	38,0	171,0