



**Motori asincroni trifase autofrenanti serie AT**  
**AT series three-phase induction brake motors**  
**Moteurs asynchrones triphasés autofreinants série AT**  
**Asynchrone Drehstrombremsmotoren Serie AT**

**8 POLI** 750 rpm - Volt 230/400/50 Hz

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	∅	Watt	Kg	Nm	∅	VA	Kg	Nm	∅	Watt	Kg	Nm	∅	Watt	Kg
AT56B	1	27000	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
AT63B	4	22500	20	6,0	5	22500	40	6,0	3	22500	17	5,0	7,5	22500	11,5	4,5
AT63C	4	22500	20	6,0	5	22500	40	6,0	3	22500	17	6,0	7,5	22500	11,5	4,9
AT71B	4	27000	20	7,0	5	27000	40	7,0	4	27000	17	7,0	7,5	27000	11,5	6,3
AT71C	4	27000	20	8,0	5	27000	40	8,0	4	27000	17	8,0	7,5	27000	11,5	7,0
AT80A	8	27000	25	11,0	10	27000	70	11,0	9	27000	34	10,0	15,0	27000	16,0	9,9
AT80B	8	27000	25	13,0	10	27000	70	13,0	9	27000	34	13,0	15,0	27000	16,0	11,6
AT80C	8	25500	25	14,0	10	25500	70	14,0	9	25500	34	14,0	15,0	25500	16,0	12,1
AT90S	16	18000	30	17,0	20	18000	120	17,0	10	18000	34	15,0	30,0	18000	16,0	14,0
AT90L	16	15000	30	18,0	20	15000	120	18,0	10	15000	34	17,0	30,0	15000	16,0	16,0
AT90LB	16	14500	30	20,0	20	14500	120	20,0	10	14500	34	19,0	30,0	14500	16,0	18,0
AT100A	32	12500	40	26,0	40	12500	160	28,0	12	12500	40	24,0	60,0	12500	21,0	23,3
AT100B	32	8500	40	29,0	40	8500	160	31,0	12	8500	40	26,0	60,0	8500	21,0	25,5
AT100BL	32	8000	40	31,0	40	8000	160	33,0	12	8000	40	28,0	60,0	8000	21,0	27,5
AT112A	60	6500	50	41,0	60	6500	300	41,0	13	6500	40	36,0	120,0	6500	21,0	38,0
AT132S	80	1900	55	57,0	90	1900	500	58,0	17	1900	40	49,0	240,0	1900	28,0	56,0
AT132M	80	1900	55	66,0	90	1900	500	67,0	17	1900	40	58,0	240,0	1900	28,0	65,0
AT132ML	80	1900	55	71,0	90	1900	500	72,0	17	1900	40	63,0	240,0	1900	28,0	70,0
AT160MA	150	1600	85	83,0	200	1600	600	81,0	30	1600	65	71,0	480,0	1600	38,0	85,0
AT160MB	150	1600	85	91,0	200	1600	600	89,0	30	1600	65	79,0	480,0	1600	38,0	93,0
AT160L	150	1600	85	105,0	200	1600	600	103,0	30	1600	65	93,0	480,0	1600	38,0	107,0
AT180L	260	200	100	119,0	400	200	600	139,0	-	-	-	-	480,0	1300	38,0	141,0
AT200LA	400	100	100	149,0	400	100	600	164,0	-	-	-	-	480,0	900	38,0	166,0