



Motori asincroni trifase doppia polarit  autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphas s   double polarit  autofreinants s rie AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

4/8 POLI 1500/750 rpm - Volt 400/50 Hz - Unico avvolgimento / Single winding

TIPO TYPE	DC				AC				DC - S				POS.DC				
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	
	Nm	�O	Watt	Kg	Nm	�O	VA	Kg	Nm	�O	Watt	Kg	Nm	�O	Watt	Kg	
AD63C	4	4	9900	20	6,0	5	9900	40	6,0	3	9900	17	-	8,0	9900	11,5	5,0
	8	4	27000	20	6,0	5	27000	40	6,0	3	27000	17	-	8,0	27000	11,5	5,0
AD71B	4	4	9900	20	8,0	5	9900	40	8,0	4	9900	17	7,6	8,0	9900	11,5	7,0
	8	4	27000	20	8,0	5	27000	40	8,0	4	27000	17	7,6	8,0	27000	11,5	7,0
AD71C	4	4	9000	20	9,0	5	9000	40	9,0	4	9000	17	8,8	8,0	9000	11,5	8,0
	8	4	25000	20	9,0	5	25000	40	9,0	4	25000	17	8,8	8,0	25000	11,5	8,0
AD80A	4	8	8000	25	11,0	8	8000	70	11,0	9	8000	34	10,9	15,0	8000	16,0	9,7
	8	8	20000	25	11,0	8	20000	70	11,0	9	20000	34	10,9	15,0	20000	16,0	9,7
AD80B	4	8	8000	25	15,0	8	8000	70	15,0	9	8000	34	12,1	15,0	8000	16,0	11,0
	8	8	20000	25	15,0	8	20000	70	15,0	9	20000	34	12,1	15,0	20000	16,0	11,0
AD80C	4	8	7500	25	15,6	8	7500	70	15,6	9	7500	34	12,7	15,0	7500	16,0	11,5
	8	8	19000	25	15,6	8	19000	70	15,6	9	19000	34	12,7	15,0	19000	16,0	11,5
AD90S	4	16	9000	30	17,0	16	9000	120	17,0	10	9000	34	14,7	30,0	9000	16,0	14,5
	8	16	13500	30	17,0	16	13500	120	17,0	10	13500	34	14,7	30,0	13500	16,0	14,5
AD90L	4	16	7500	30	19,0	16	7500	120	19,0	10	7500	34	16,2	30,0	7500	16,0	16,0
	8	16	11500	30	19,0	16	11500	120	19,0	10	11500	34	16,2	30,0	11500	16,0	16,0
AD90LB	4	16	7000	30	21,5	16	7000	120	21,5	10	7000	34	18,2	30,0	7000	16,0	18,5
	8	16	10500	30	21,5	16	10500	120	21,5	10	10500	34	18,2	30,0	10500	16,0	18,5
AD100A	4	32	3700	40	27,0	45	3700	160	29,0	12	3700	40	23,8	60,0	3700	21,0	23,6
	8	32	7700	40	27,0	45	7700	160	29,0	12	7700	40	23,8	60,0	7700	21,0	23,6
AD100B	4	32	3500	40	29,0	45	3500	160	31,0	12	3500	40	25,5	60,0	3500	21,0	25,3
	8	32	7400	40	29,0	45	7400	160	31,0	12	7400	40	25,5	60,0	7400	21,0	25,3
AD112A	4	60	3400	50	41,0	70	3400	300	41,0	13	3400	40	35,7	120,0	3400	21,0	38,0
	8	60	7200	50	41,0	70	7200	300	41,0	13	7200	40	35,7	120,0	7200	21,0	38,0
AD112B	4	60	3200	50	46,0	70	3200	300	46,0	13	3200	40	40,7	120,0	3200	21,0	43,0
	8	60	6800	50	46,0	70	6800	300	46,0	13	6800	40	40,7	120,0	6800	21,0	43,0
AD132S	4	80	900	55	59,0	95	900	500	60,0	17	900	40	50,5	240,0	900	28,0	57,5
	8	80	1600	55	59,0	95	1600	500	60,0	17	1600	40	50,5	240,0	1600	28,0	57,5
AD132M	4	80	900	55	69,0	95	900	500	70,0	17	900	40	60,5	240,0	900	28,0	67,5
	8	80	1600	55	69,0	95	1600	500	70,0	17	1600	40	60,5	240,0	1600	28,0	67,5
AD132ML	4	80	900	55	71,0	95	900	500	72,0	17	900	40	62,5	240,0	900	28,0	69,5
	8	80	1600	55	71,0	95	1600	500	72,0	17	1600	40	62,5	240,0	1600	28,0	69,5
AD160M	4	150	850	85	93,0	150	850	600	91,0	23	850	45	81,0	480,0	850	38,0	94,5
	8	150	1500	85	93,0	150	1500	600	91,0	23	1500	45	81,0	480,0	1500	38,0	94,5
AD160L	4	150	850	85	109,0	150	850	600	107,0	23	850	45	97,0	480,0	850	38,0	110,5
	8	150	1500	85	109,0	150	1500	600	107,0	23	1500	45	97,0	480,0	1500	38,0	110,5
AD160LB	4	150	850	85	129,0	150	850	600	127,0	23	850	45	117,0	480,0	850	38,0	130,5
	8	150	1500	85	129,0	150	1500	600	127,0	23	1500	45	117,0	480,0	1500	38,0	130,5
AD180L	4	260	200	100	145,0	300	200	600	144,0	-	-	-	-	480,0	200	-	145,5
	8	260	200	100	145,0	300	200	600	144,0	-	-	-	-	480,0	200	-	145,5
AD200L	4	400	100	100	170,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5
	8	400	100	100	170,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5