



**Motori asincroni trifase doppia polarit  autofrenanti serie AD**  
**AD series two-speed three-phase induction brake motors**  
**Moteurs asynchrones triphas s   double polarit  autofreinants s rie AD**  
**Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD**

**4/6 POLI 1500/1000 rpm - Volt 400/50 Hz - Unico avvolgimento PAM / PAM single winding**

TIPO TYPE	DC				AC				DC - S				POS.DC				
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	
	Nm	��	Watt	Kg	Nm	��	VA	Kg	Nm	��	Watt	Kg	Nm	��	Watt	Kg	
AD71B	4	4	6700	20	8,0	5	6700	40	8,0	4	6700	17	-	8,0	6700	11,5	-
	6	4	13500	20	8,0	5	13500	40	8,0	4	13500	17	-	8,0	13500	11,5	-
AD71C	4	4	6700	20	9,0	5	6700	40	9,0	4	6700	17	8,80	8,0	6700	11,5	8,0
	6	4	13500	20	9,0	5	13500	40	9,0	4	13500	17	8,80	8,0	13500	11,5	8,0
AD80A	4	8	6300	25	11,0	8	6300	70	11,0	9	6300	34	10,90	8,0	6300	16,0	9,7
	6	8	13500	25	11,0	8	13500	70	11,0	9	13500	34	10,90	8,0	13500	16,0	9,7
AD80B	4	8	6300	25	13,0	8	6300	70	13,0	9	6300	34	12,10	15,0	6300	16,0	11,0
	6	8	13500	25	13,0	8	13500	70	13,0	9	13500	34	12,10	15,0	13500	16,0	11,0
AD90S	4	16	5400	30	17,0	16	5400	120	17,0	10	5400	34	14,70	30,0	5400	16,0	14,5
	6	16	11000	30	17,0	16	11000	120	17,0	10	11000	34	14,70	30,0	11000	16,0	14,5
AD90L	4	16	5000	30	19,0	16	5000	120	19,0	10	5000	34	16,20	30,0	5000	16,0	16,0
	6	16	9000	30	19,0	16	9000	120	19,0	10	9000	34	16,20	30,0	9000	16,0	16,0
AD90LB	4	16	4500	30	21,0	16	4500	120	21,0	10	4500	34	18,20	30,0	4500	16,0	18,0
	6	16	8000	30	21,0	16	8000	120	21,0	10	8000	34	18,20	30,0	8000	16,0	18,0
AD100A	4	32	1800	40	25,5	45	1800	160	27,5	12	1800	40	22,50	60,0	1800	21,0	22,3
	6	32	4500	40	25,5	45	4500	160	27,5	12	4500	40	22,50	60,0	4500	21,0	22,3
AD100B	4	32	1600	40	29,0	45	1600	160	33,0	12	1600	40	25,50	60,0	1600	21,0	25,3
	6	32	4000	40	29,0	45	4000	160	33,0	12	4000	40	25,50	60,0	4000	21,0	25,3
AD112A	4	60	1500	50	41,0	70	1500	300	41,0	13	1500	40	35,70	120,0	1500	21,0	38,0
	6	60	3600	50	41,0	70	3600	300	41,0	13	3600	40	35,70	120,0	3600	21,0	38,0
AD112B	4	60	1500	50	45,0	70	1500	300	47,0	13	1500	40	41,73	120,0	1500	21,0	44,0
	6	60	3600	50	45,0	70	3600	300	47,0	13	3600	40	41,73	120,0	3600	21,0	44,0
AD132S	4	80	540	55	57,0	95	540	500	58,0	17	540	40	48,50	240,0	540	28,0	55,5
	6	80	900	55	57,0	95	900	500	58,0	17	900	40	48,50	240,0	900	28,0	55,5
AD132M	4	80	540	55	65,0	95	540	500	66,0	17	540	40	56,50	240,0	540	28,0	63,5
	6	80	900	55	65,0	95	900	500	66,0	17	900	40	56,50	240,0	900	28,0	63,5
AD160M	4	150	450	85	93,0	150	450	600	98,0	23	450	45	81,00	480,0	450	38,0	100,5
	6	150	800	85	93,0	150	800	600	98,0	23	800	45	81,00	480,0	800	38,0	100,5
AD160L	4	150	450	85	109,0	150	450	600	114,0	23	450	45	97,00	480,0	450	38,0	110,5
	6	150	800	85	109,0	150	800	600	114,0	23	800	45	97,00	480,0	800	38,0	110,5
AD180M	4	260	200	100	134,0	300	200	600	134,0	-	-	-	-	480,0	200	-	135,5
	6	260	200	100	134,0	300	200	600	134,0	-	-	-	-	480,0	200	-	135,5
AD180L	4	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
	6	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
AD200L	4	400	100	100	169,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5
	6	400	100	100	169,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5