



Motori asincroni trifase doppia polarità autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphasés à double polarité autofreinants série AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

6/8 POLI 1000/750 rpm - Volt 400/50 Hz - Doppio avvolgimento / Double winding

TIPO TYPE	DC					AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight		CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	ωO	Watt	Kg	Nm	ωO	VA	Kg	Nm	ωO	Watt	Kg	Nm	ωO	Watt	Kg	Nm
AD63C	6	4	4500	20	6,0	5	4500	40	7,0	3	4500	17	5,7	8,0	4500	11,5	4,8
	8	4	5500	20	6,0	5	5500	40	7,0	3	5500	17	5,7	8,0	5500	11,5	4,8
AD71C	6	4	5500	20	8,0	5	5500	40	8,4	4	5500	17	7,9	8,0	5500	11,5	7,6
	8	4	14000	20	8,0	5	14000	40	8,4	4	14000	17	7,9	8,0	14000	11,5	7,6
AD80A	6	8	2700	25	10,7	8	2700	70	11,0	9	2700	34	10,9	15,0	2700	16,0	10,7
	8	8	9000	25	10,7	8	9000	70	11,0	9	9000	34	10,9	15,0	9000	16,0	10,7
AD80B	6	8	2500	25	13,0	8	2500	70	12,2	9	2500	34	12,1	15,0	2500	16,0	13,0
	8	8	8500	25	13,0	8	8500	70	12,2	9	8500	34	12,1	15,0	8500	16,0	13,0
AD90S	6	16	2500	30	15,5	16	2500	120	17,0	10	2500	34	14,7	30,0	2500	16,0	15,5
	8	16	8500	30	15,5	16	8500	120	17,0	10	8500	34	14,7	30,0	8500	16,0	15,5
AD90L	6	16	2300	30	17,0	16	2300	120	18,0	10	2300	34	16,2	30,0	2300	16,0	14,6
	8	16	8000	30	17,0	16	8000	120	18,0	10	8000	34	16,2	30,0	8000	16,0	14,6
AD90LB	6	16	2300	30	21,0	16	2300	120	22,0	10	2300	34	20,2	30,0	2300	16,0	16,6
	8	16	7800	30	21,0	16	7800	120	22,0	10	7800	34	20,2	30,0	7800	16,0	16,6
AD100A	6	32	1600	40	23,0	45	1600	160	25,5	12	1600	40	22,5	60,0	1600	21,0	23,0
	8	32	6000	40	23,0	45	6000	160	25,5	12	6000	40	22,5	60,0	6000	21,0	23,0
AD100B	6	32	1500	40	26,0	45	1500	160	29,0	12	1500	40	25,5	60,0	1500	21,0	25,0
	8	32	5500	40	26,0	45	5500	160	29,0	12	5500	40	25,5	60,0	5500	21,0	25,0
AD112A	6	60	1200	50	38,0	70	1200	300	41,0	13	1200	40	35,7	120,0	1200	21,0	39,0
	8	60	3400	50	38,0	70	3400	300	41,0	13	3400	40	35,7	120,0	3400	21,0	39,0
AD132S	6	60	900	55	54,0	95	900	500	60,0	17	900	40	49,5	240,0	900	28,0	57,0
	8	60	1600	55	54,0	95	1600	500	60,0	17	1600	40	49,5	240,0	1600	28,0	57,0
AD132M	6	80	900	55	64,0	95	900	500	69,0	17	900	40	60,0	240,0	900	28,0	67,0
	8	80	1600	55	64,0	95	1600	500	69,0	17	1600	40	60,0	240,0	1600	28,0	67,0
AD160M	6	150	800	85	84,0	150	800	600	87,0	23	800	45	75,0	480,0	800	38,0	92,0
	8	150	1500	85	84,0	150	1500	600	87,0	23	1500	45	75,0	480,0	1500	38,0	92,0
AD160L	6	150	600	85	104,0	150	600	600	107,0	23	600	45	95,0	480,0	600	38,0	112,0
	8	150	1000	85	104,0	150	1000	600	107,0	23	1000	45	95,0	480,0	1000	38,0	112,0
AD180L	6	260	200	100	150,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
	8	260	200	100	150,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
AD200L	6	400	100	100	170,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5
	8	400	100	100	170,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5