



Motori asincroni trifase doppia polarità autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphasés à double polarité autofreinants série AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

2/6 POLI 3000/1000 rpm - Volt 400/50 Hz - Doppio avvolgimento / Double winding

TIPO TYPE	DC				AC				DC - S				POS.DC				
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	
	Nm	ωO	Watt	Kg	Nm	ωO	VA	Kg	Nm	ωO	Watt	Kg	Nm	ωO	Watt	Kg	
AD63C	2	4	2800	20	6,1	5	2800	40	6,1	3	2800	17	5,8	8,0	2800	11,5	4,8
	6	4	12000	20	6,1	5	12000	40	6,1	3	12000	17	5,8	8,0	12000	11,5	4,8
AD71C	2	4	2700	20	8,0	5	2700	40	8,0	4	2700	17	7,6	8,0	2700	11,5	7,3
	6	4	11000	20	8,0	5	11000	40	8,0	4	11000	17	7,6	8,0	11000	11,5	7,3
AD80A	2	8	1800	25	11,0	8	1800	70	11,0	9	1800	34	10,9	15,0	1800	16,0	9,7
	6	8	13500	25	11,0	8	13500	70	11,0	9	13500	34	10,9	15,0	13500	16,0	9,7
AD80B	2	8	1800	25	13,0	8	1800	70	13,0	9	1800	34	11,2	15,0	1800	16,0	11,0
	6	8	13500	25	13,0	8	13500	70	13,0	9	13500	34	11,2	15,0	13500	16,0	11,0
AD90S	2	16	1600	30	17,0	16	1600	120	17,0	10	1600	34	14,7	30,0	1600	16,0	15,0
	6	16	13500	30	17,0	16	13500	120	17,0	10	13500	34	14,7	30,0	13500	16,0	15,0
AD90L	2	16	1600	30	19,0	16	1600	120	19,0	10	1600	34	16,2	30,0	1600	16,0	16,5
	6	16	12000	30	19,0	16	12000	120	19,0	10	12000	34	16,2	30,0	12000	16,0	16,5
AD90LB	2	16	1600	30	21,0	16	1600	120	21,0	10	1600	34	18,2	30,0	1600	16,0	18,5
	6	16	11000	30	21,0	16	11000	120	21,0	10	11000	34	18,2	30,0	11000	16,0	18,5
AD100A	2	32	1600	40	25,5	45	1600	160	27,5	12	1600	40	22,5	60,0	1600	21,0	23,0
	6	32	13000	40	25,5	45	13000	160	27,5	12	13000	40	22,5	60,0	13000	21,0	23,0
AD100B	2	32	900	40	29,0	45	900	160	31,0	12	900	40	25,5	60,0	900	21,0	26,0
	6	32	13000	40	29,0	45	13000	160	31,0	12	13000	40	25,5	60,0	13000	21,0	26,0
AD112A	2	60	900	50	41,0	70	900	300	41,0	13	900	40	35,7	120,0	900	21,0	39,0
	6	60	7700	50	41,0	70	7700	300	41,0	13	7700	40	35,7	120,0	7700	21,0	39,0
AD132S	2	80	300	55	57,0	95	300	500	58,0	13	300	40	58,5	240,0	300	28,0	56,0
	6	80	1500	55	57,0	95	1500	500	58,0	13	1500	40	58,5	240,0	1500	28,0	56,0
AD132M	2	80	300	55	66,0	95	300	500	67,0	17	300	40	57,5	240,0	300	28,0	65,0
	6	80	1500	55	66,0	95	1500	500	67,0	17	1500	40	57,5	240,0	1500	28,0	65,0
AD160M	2	150	300	85	108,0	150	300	600	106,0	23	300	45	95,0	480,0	300	38,0	91,0
	6	150	800	85	108,0	150	800	600	106,0	23	800	45	95,0	480,0	800	38,0	91,0
AD160L	2	150	300	85	119,0	150	300	600	117,0	23	300	45	106,0	480,0	300	38,0	101,0
	6	150	600	85	119,0	150	600	600	117,0	23	600	45	106,0	480,0	600	38,0	101,0
AD180M	2	260	200	100	134,0	300	200	600	134,0	-	-	-	-	480,0	200	-	135,5
	6	260	200	100	134,0	300	200	600	134,0	-	-	-	-	480,0	200	-	135,5
AD180L	2	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
	6	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
AD200L	2	400	100	100	169,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5
	6	400	100	100	169,0	300	100	600	169,0	-	-	-	-	480,0	100	-	170,5