



Motori asincroni trifase doppia polarit  autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphas s   double polarit  autofreinants s rie AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

2/8 POLI 3000/750 rpm - Volt 400/50 Hz - Doppio avvolgimento / Double winding

TIPO TYPE	DC					AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight		CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	�O	Watt	Kg	Nm	�O	VA	Kg	Nm	�O	Watt	Kg	Nm	�O	Watt	Kg	
AD63C	2	4	2250	20	6,0	5	2250	40	6,0	3	2250	17	5,4	8,0	2250	11,5	5,4
	8	4	16000	20	6,0	5	16000	40	6,0	3	16000	17	5,4	8,0	16000	11,5	5,4
AD71C	2	4	2700	20	8,0	5	2700	40	8,0	4	2700	17	7,6	8,0	2700	11,5	7,3
	8	4	20000	20	8,0	5	20000	40	8,0	4	20000	17	7,6	8,0	20000	11,5	7,3
AD80A	2	8	1800	25	11,0	8	1800	70	11,0	9	1800	34	10,9	15,0	1800	16,0	10,0
	8	8	18000	25	11,0	8	18000	70	11,0	9	18000	34	10,9	15,0	18000	16,0	10,0
AD80B	2	8	1800	25	13,0	8	1800	70	13,0	9	1800	34	12,1	15,0	1800	16,0	11,0
	8	8	18000	25	13,0	8	18000	70	13,0	9	18000	34	12,1	15,0	18000	16,0	11,0
AD90S	2	16	1600	30	17,0	16	1600	120	17,0	10	1600	34	14,7	30,0	1600	16,0	15,0
	8	16	16000	30	17,0	16	16000	120	17,0	10	16000	34	14,7	30,0	16000	16,0	15,0
AD90L	2	16	1600	30	19,0	16	1600	120	19,0	10	1600	34	16,2	30,0	1600	16,0	16,0
	8	16	15000	30	19,0	16	15000	120	19,0	10	15000	34	16,2	30,0	15000	16,0	16,0
AD90LB	2	16	1600	30	21,0	16	1600	120	21,0	10	1600	34	18,2	30,0	1600	16,0	18,0
	8	16	14000	30	21,0	16	14000	120	21,0	10	14000	34	18,2	30,0	14000	16,0	18,0
AD100A	2	32	900	40	25,5	45	900	160	27,5	12	900	40	22,5	60,0	900	21,0	23,0
	8	32	9000	40	25,5	45	9000	160	27,5	12	9000	40	22,5	60,0	9000	21,0	23,0
AD100B	2	32	900	40	29,0	45	900	160	31,0	12	900	40	25,5	60,0	900	21,0	26,0
	8	32	9000	40	29,0	45	9000	160	31,0	12	9000	40	25,5	60,0	9000	21,0	26,0
AD112A	2	60	950	50	42,0	70	950	300	42,0	13	950	40	36,7	120,0	950	21,0	40,0
	8	60	8000	50	42,0	70	8000	300	42,0	13	8000	40	36,7	120,0	8000	21,0	40,0
AD132S	2	80	400	55	57,0	95	400	500	58,0	17	400	40	46,5	240,0	400	28,0	56,0
	8	80	1600	55	57,0	95	1600	500	58,0	17	1600	40	46,5	240,0	1600	28,0	56,0
AD132M	2	80	350	55	66,0	95	350	500	67,0	17	350	40	56,5	240,0	350	28,0	64,0
	8	80	1600	55	66,0	95	1600	500	67,0	17	1600	40	56,5	240,0	1600	28,0	64,0
AD160M	2	150	300	85	108,0	150	300	600	106,0	23	300	45	95,0	480,0	300	38,0	91,0
	8	150	1500	85	108,0	150	1500	600	106,0	23	1500	45	95,0	480,0	1500	38,0	91,0
AD160L	2	150	300	85	119,0	150	300	600	117,0	23	300	45	106,0	480,0	300	38,0	111,0
	8	150	1000	85	119,0	150	1000	600	117,0	23	1000	45	106,0	480,0	1000	38,0	111,0
AD180L	2	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
	8	260	200	100	149,0	300	200	600	149,0	-	-	-	-	480,0	200	-	150,5
AD200L	2	400	100	100	169,0	300	100	600	169,0	-	-	-	-	480,0	100	-	181,0
	8	400	100	100	169,0	300	100	600	169,0	-	-	-	-	480,0	100	-	181,0