



Motori asincroni trifase doppia polarit  autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphas s   double polarit  autofreinants s rie AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

2/12 POLI 3000/500 rpm - Volt 400/50 Hz - Doppio avvolgimento / Double winding

TIPO TYPE	DC				AC				DC - S				POS.DC				
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	
	Nm	�O	Watt	Kg	Nm	�O	VA	Kg	Nm	�O	Watt	Kg	Nm	�O	Watt	Kg	
AD71C	2	4	24000	20	9,3	5	24000	40	9,3	4	24000	17	9,1	8,0	24000	11,5	8,8
	12	4	27000	20	9,3	5	27000	40	9,3	4	27000	17	9,1	8,0	27000	11,5	8,8
AD80B	2	8	16000	25	11,0	8	16000	70	12,0	9	16000	34	11,0	15,0	16000	16,0	10,8
	12	8	27000	25	11,0	8	27000	70	12,0	9	27000	34	11,0	15,0	27000	16,0	10,8
AD80C	2	8	15000	25	13,0	8	15000	70	12,5	9	15000	34	12,7	15,0	15000	16,0	12,5
	12	8	25500	25	13,0	8	25500	70	12,5	9	25500	34	12,7	15,0	25500	16,0	12,5
AD90L	2	16	15000	30	15,0	16	15000	120	16,0	10	15000	34	14,2	30,0	15000	16,0	15,0
	12	16	18000	30	15,0	16	18000	120	16,0	10	18000	34	14,2	30,0	18000	16,0	15,0
AD90LB	2	16	13000	30	17,0	16	13000	120	18,0	10	13000	34	16,2	30,0	13000	16,0	17,0
	12	16	14500	30	17,0	16	14500	120	18,0	10	14500	34	16,2	30,0	14500	16,0	17,0
AD100BL	2	32	7500	40	28,5	45	7500	160	28,5	12	7500	40	25,5	60,0	7500	21,0	26,0
	12	32	8500	40	28,5	45	8500	160	28,5	12	8500	40	25,5	60,0	8500	21,0	26,0
AD112B	2	60	1400	50	41,0	70	1400	300	41,0	13	1400	40	36,0	120,0	1400	21,0	40,0
	12	60	6000	50	41,0	70	6000	300	41,0	13	6000	40	36,0	120,0	6000	21,0	40,0
AD132S	2	80	430	55	54,0	95	430	500	57,0	17	430	40	58,0	240,0	430	28,0	58,0
	12	80	2000	55	54,0	95	2000	500	57,0	17	2000	40	58,0	240,0	2000	28,0	58,0
AD132M	2	80	400	55	62,0	95	400	500	65,0	17	400	40	59,0	240,0	400	28,0	66,0
	12	80	2000	55	62,0	95	2000	500	65,0	17	2000	40	59,0	240,0	2000	28,0	66,0
AD160M	2	150	300	85	95,0	150	300	600	96,0	23	300	45	95,0	480,0	300	38,0	102,0
	12	150	1650	85	95,0	150	1650	600	96,0	23	1650	45	95,0	480,0	1650	38,0	102,0
AD160L	2	150	300	85	105,0	150	300	600	106,0	23	300	45	106,0	480,0	300	38,0	112,0
	12	150	1650	85	105,0	150	1650	600	106,0	23	1650	45	106,0	480,0	1650	38,0	112,0
AD180L	2	260	200	100	150,0	300	200	600	150,0	-	-	-	-	480,0	200	-	152,0
	12	260	200	100	150,0	300	200	600	150,0	-	-	-	-	480,0	200	-	152,0
AD200L	2	400	100	100	170,0	300	100	600	180,0	-	-	-	-	480,0	100	-	182,0
	12	400	100	100	170,0	300	100	600	180,0	-	-	-	-	480,0	100	-	182,0