



Motori asincroni trifase doppia polarit  autofrenanti serie AD
AD series two-speed three-phase induction brake motors
Moteurs asynchrones triphas s   double polarit  autofreinants s rie AD
Polumschaltbare asynchrone Drehstrombremsmotoren Serie AD

2/16 POLI 3000/375 rpm - Volt 400/50 Hz - Doppio avvolgimento / Double winding

TIPO TYPE	DC				AC				DC - S				POS.DC				
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	
	Nm	��	Watt	Kg	Nm	��	VA	Kg	Nm	��	Watt	Kg	Nm	��	Watt	Kg	
AD132S	2	80	430	55	54	95	430	500	57	17	430	40	58	240	430	28	58,0
	16	80	2000	55	54	95	2000	500	57	17	2000	40	58	240	2000	28	58,0
AD132M	2	80	400	55	62	95	400	500	65	17	400	40	59	240	400	28	66,0
	16	80	2000	55	62	95	2000	500	65	17	2000	40	59	240	2000	28	66,0
AD160M	2	150	300	85	95	150	300	600	96	23	300	45	95	480	300	38	102,0
	16	150	1650	85	95	150	1650	600	96	23	1650	45	95	480	1650	38	102,0
AD160L	2	150	300	85	105	150	300	600	106	23	300	45	106	480	300	38	112,0
	16	150	1650	85	105	150	1650	600	106	23	1650	45	106	480	1650	38	112,0
AD180L	2	260	200	100	150	300	200	600	150	-	-	-	-	480	200	-	152,0
	16	260	200	100	150	300	200	600	150	-	-	-	-	480	200	-	152,0
AD200L	2	400	100	100	170	300	100	600	180	-	-	-	-	480	100	-	182,0
	16	400	100	100	170	300	100	600	180	-	-	-	-	480	100	-	182,0